



**Catalog**

- ▶ [Home](#)
- ▶ [Part Number Search](#)
- ▶ [Document Search](#)
- ▶ [CAD Model Search](#)
- ▶ [Text Search](#)
- ▶ [Alternate Part Search](#)
- ▶ [Multiple Part Comparison](#)
- ▶ [Alphabetical Search](#)
- ▶ [Brand Search](#)
- ▶ [Industry Product Search](#)
- ▶ [Product Type Search](#)
- ▶ [Product Family Search](#)
- ▶ [Competitor Cross Reference](#)
- ▶ [Lead Free Solutions](#)
- ▶ [Help/Glossary](#)

**Soft Shell Connectors**

↳ **.250" Centerline, 600 V, 19 A max. (Universal MATE-N-LOK)**

**AMP 350689-2** [Active](#)

**Directive 2002/95/EC Compliant**

[RoHS Compliant](#)

**(Tyco Electronics P/N: 350689-2)**

[CAD Geometry](#) | [Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li>▶ <a href="#">General Info</a></li> <li>▶ <a href="#">Sales Info</a></li> <li>▶ <a href="#">Assembly Subcontractors</a></li> </ul>	<ul style="list-style-type: none"> <li>▶ <a href="#">Pricing</a></li> <li>▶ <a href="#">Product Availability</a></li> </ul>	<ul style="list-style-type: none"> <li>▶ <a href="#">Tooling</a></li> </ul>

**Photos & Line Drawings** - The photographs and/or line drawings are representative images of a product for viewing purposes only.



**Searchable Features:**

<b>Brand:</b>	AMP
<b>Product Type:</b>	Contact
<b>Connector Line:</b>	Universal MATE-N-LOK
<b>CompactPCI:</b>	No
<b>Contact Type:</b>	Socket
<b>High Current:</b>	No
<b>Wire Range (mm [AWG]):</b>	0.20-0.80 <sup>2</sup> [24-18]
<b>Insulation Diameter (mm [in]):</b>	1.02-2.54 [.040-.100]
<b>Contact Material:</b>	Brass
<b>Sealable:</b>	No

**Other Properties:**

<b>Contact Diameter (mm [in]):</b>	2.13 [0.084]
<b>Packaging Method:</b>	Loose Piece
<b>Contact Termination Area Plating:</b>	Gold (30)
<b>Stock Thickness (mm [in]):</b>	0.25 [0.010]
<b>Voltage (VAC):</b>	600
<b>Comment:</b>	Contacts can be used with Splash Proof Seals if insulation diameter range is .060-.100.

**Current Rating  
(Amps.):**

19

---

[Copyright](#) and [Privacy Statement](#)

Visit [Tyco International, Ltd.](#)

[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)